


American Standard Fractional Horsepower (FHP) V-Belts



3L



4L

3L

Manufacturing Range 11* - 80"


Part No.	Outside Length (inches)	Wt. (lbs)	Part No.	Outside Length (inches)	Wt. (lbs)	Part No.	Outside Length (inches)	Wt. (lbs)	Part No.	Outside Length (inches)	Wt. (lbs)
3L110	11	0.05	3L280	28	0.12	3L440	44	0.19	3L640	64	0.28
3L120	12	0.05	3L285	28.5	0.13	3L450	45	0.20	3L650	65	0.29
3L130	13	0.06	3L290	29	0.13	3L460	46	0.20	3L660	66	0.29
3L140	14	0.06	3L293	29.3	0.13	3L470	47	0.21	3L670	67	0.29
3L150	15	0.07	3L300	30	0.13	3L480	48	0.21	3L675	67.5	0.30
3L160	16	0.07	3L310	31	0.14	3L490	49	0.22	3L680	68	0.30
3L170	17	0.07	3L320	32	0.14	3L500	50	0.22	3L690	69	0.30
3L180	18	0.08	3L330	33	0.15	3L510	51	0.22	3L700	70	0.31
3L190	19	0.08	3L340	34	0.15	3L520	52	0.23	3L710	71	0.31
3L200	20	0.09	3L345	34.5	0.15	3L530	53	0.23	3L720	72	0.32
3L210	21	0.09	3L350	35	0.15	3L540	54	0.24	3L730	73	0.32
3L220	22	0.10	3L360	36	0.16	3L550	55	0.24	3L740	74	0.33
3L225	22.5	0.10	3L370	37	0.16	3L560	56	0.25	3L750	75	0.33
3L230	23	0.10	3L380	38	0.17	3L565	56.5	0.25	3L760	76	0.33
3L240	24	0.11	3L385	38.5	0.17	3L570	57	0.25	3L765	76.5	0.34
3L245	24.5	0.11	3L390	39	0.17	3L580	58	0.26	3L770	77	0.34
3L250	25	0.11	3L400	40	0.18	3L590	59	0.26	3L780	78	0.34
3L255	25.5	0.11	3L410	41	0.18	3L595	59.5	0.26	3L790	79	0.35
3L260	26	0.11	3L415	41.5	0.18	3L600	60	0.26	3L800	80	0.35
3L265	26.5	0.12	3L420	42	0.18	3L610	61	0.27			
3L270	27	0.12	3L425	42.5	0.19	3L620	62	0.27			
3L275	27.5	0.12	3L430	43	0.19	3L630	63	0.28			

4L

Manufacturing Range 15* - 400"

Part No.	Outside Length (inches)	Wt. (lbs)	Part No.	Outside Length (inches)	Wt. (lbs)	Part No.	Outside Length (inches)	Wt. (lbs)	Part No.	Outside Length (inches)	Wt. (lbs)
4L150	15	0.08	4L325	32.5	0.18	4L520	52	0.29	4L770	77	0.43
4L170	17	0.10	4L330	33	0.19	4L525	52.5	0.30	4L780	78	0.44
4L180	18	0.10	4L335	33.5	0.19	4L530	53	0.30	4L790	79	0.44
4L190	19	0.11	4L340	34	0.19	4L540	54	0.30	4L800	80	0.45
4L195	19.5	0.11	4L345	34.5	0.19	4L550	55	0.31	4L810	81	0.46
4L200	20	0.11	4L350	35	0.20	4L560	56	0.32	4L820	82	0.46
4L210	21	0.12	4L360	36	0.20	4L570	57	0.32	4L830	83	0.47
4L215	21.5	0.12	4L370	37	0.21	4L580	58	0.33	4L840	84	0.47
4L220	22	0.12	4L380	38	0.21	4L590	59	0.33	4L850	85	0.48
4L230	23	0.13	4L390	39	0.22	4L600	60	0.34	4L860	86	0.48
4L235	23.5	0.13	4L400	40	0.23	4L610	61	0.34	4L870	87	0.49
4L240	24	0.14	4L405	40.5	0.23	4L620	62	0.35	4L880	88	0.50
4L250	25	0.14	4L410	41	0.23	4L630	63	0.35	4L890	89	0.50
4L255	25.5	0.14	4L415	41.5	0.23	4L640	64	0.36	4L900	90	0.51
4L260	26	0.15	4L420	42	0.24	4L650	65	0.37	4L910	91	0.51
4L270	27	0.15	4L430	43	0.24	4L660	66	0.37	4L920	92	0.52
4L275	27.5	0.15	4L440	44	0.25	4L670	67	0.38	4L930	93	0.52
4L280	28	0.16	4L450	45	0.25	4L680	68	0.38	4L940	94	0.53
4L285	28.5	0.16	4L460	46	0.26	4L690	69	0.39	4L950	95	0.54
4L290	29	0.16	4L470	47	0.26	4L700	70	0.39	4L960	96	0.54
4L295	29.5	0.17	4L475	47.5	0.27	4L710	71	0.40	4L970	97	0.55
4L300	30	0.17	4L480	48	0.27	4L720	72	0.41	4L980	98	0.55
4L305	30.5	0.17	4L490	49	0.28	4L730	73	0.41	4L990	99	0.56
4L310	31	0.17	4L500	50	0.28	4L740	74	0.42	4L1000	100	0.56
4L315	31.5	0.18	4L510	51	0.29	4L750	75	0.42			
4L320	32	0.18	4L515	51.5	0.29	4L760	76	0.43			

American Standard Fractional Horsepower (FHP) V-Belts








5L

5L

Manufacturing Range 22* - 300"

Part No.	Outside Length (inches)	Wt. (lbs)	Part No.	Outside Length (inches)	Wt. (lbs)	Part No.	Outside Length (inches)	Wt. (lbs)	Part No.	Outside Length (inches)	Wt. (lbs)
5L220	22	0.22	5L415	41.5	0.41	5L620	62	0.61	5L840	84	0.83
5L230	23	0.23	5L420	42	0.42	5L630	63	0.62	5L850	85	0.84
5L240	24	0.24	5L430	43	0.43	5L640	64	0.63	5L860	86	0.85
5L250	25	0.25	5L440	44	0.44	5L650	65	0.64	5L870	87	0.86
5L260	26	0.26	5L450	45	0.45	5L660	66	0.65	5L880	88	0.87
5L270	27	0.27	5L460	46	0.46	5L670	67	0.66	5L890	89	0.88
5L280	28	0.28	5L470	47	0.47	5L680	68	0.67	5L900	90	0.89
5L290	29	0.29	5L480	48	0.48	5L690	69	0.68	5L910	91	0.90
5L300	30	0.30	5L490	49	0.49	5L700	70	0.69	5L920	92	0.91
5L310	31	0.31	5L500	50	0.50	5L710	71	0.70	5L930	93	0.92
5L320	32	0.32	5L510	51	0.50	5L720	72	0.71	5L940	94	0.93
5L330	33	0.33	5L520	52	0.51	5L730	73	0.72	5L950	95	0.94
5L340	34	0.34	5L530	53	0.52	5L740	74	0.73	5L960	96	0.95
5L350	35	0.35	5L540	54	0.53	5L750	75	0.74	5L970	97	0.96
5L355	35.5	0.35	5L550	55	0.54	5L760	76	0.75	5L980	98	0.97
5L360	36	0.36	5L560	56	0.55	5L770	77	0.76	5L990	99	0.98
5L365	36.5	0.36	5L570	57	0.56	5L780	78	0.77	5L1000	100	0.99
5L370	37	0.37	5L575	57.5	0.57	5L790	79	0.78			
5L380	38	0.38	5L580	58	0.57	5L800	80	0.79			
5L390	39	0.39	5L590	59	0.58	5L810	81	0.80			
5L400	40	0.40	5L600	60	0.59	5L820	82	0.81			
5L410	41	0.41	5L610	61	0.60	5L830	83	0.82			

American Standard Classical V-Belts



A

Section A (1/2" x 11/32")






Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)
A 18	.15	A 39	.27	A 60	.46	A 81	.56	A 102	.71	A 130	.91
A 19	.15	A 40	.28	A 61	.47	A 82	.57	A 103	.72	A 133	.94
A 20	.15	A 41	.29	A 62	.48	A 83	.58	A 104	.73	A 134	.94
A 21	.15	A 42	.29	A 63	.48	A 84	.59	A 105	.74	A 135	.95
A 22	.15	A 43	.30	A 64	.49	A 85	.59	A 106	.75	A 136	.96
A 23	.15	A 44	.31	A 65	.50	A 86	.60	A 107	.75	A 139	.98
A 24	.17	A 45	.32	A 66	.51	A 87	.61	A 108	.75	A 140	1.01
A 25	.18	A 46	.33	A 67	.51	A 88	.61	A 109	.76	A 142	1.01
A 26	.18	A 47	.34	A 68	.52	A 89	.62	A 110	.76	A 144	1.01
A 27	.19	A 48	.34	A 69	.53	A 90	.63	A 112	.78	A 150	1.10
A 28	.19	A 49	.34	A 70	.53	A 91	.64	A 113	.79	A 158	1.12
A 29	.20	A 50	.38	A 71	.53	A 92	.64	A 115	.80	A 160	1.18
A 30	.21	A 51	.39	A 72	.53	A 93	.65	A 116	.81	A 162	1.18
A 31	.22	A 52	.40	A 73	.54	A 94	.65	A 117	.82	A 173	1.20
A 32	.22	A 53	.41	A 74	.54	A 95	.66	A 118	.83	A 180	1.25
A 33	.23	A 54	.41	A 75	.54	A 96	.67	A 120	.84	A 200	1.40
A 34	.24	A 55	.42	A 76	.54	A 97	.68	A 123	.85		
A 35	.24	A 56	.43	A 77	.54	A 98	.68	A 124	.86		
A 36	.25	A 57	.43	A 78	.54	A 99	.69	A 125	.87		
A 37	.26	A 58	.44	A 79	.55	A 100	.70	A 126	.89		
A 38	.27	A 59	.45	A 80	.56	A 101	.71	A 128	.89		

B

Section B (21/32" x 7/16")

Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)
B 22	.32	B 54	.66	B 86	1.04	B 118	1.40	B 160	2.03	B 237	2.78
B 24	.32	B 55	.67	B 87	1.06	B 119	1.41	B 162	2.05	B 238	2.79
B 25	.32	B 56	.69	B 88	1.07	B 120	1.42	B 163	2.07	B 240	2.80
B 26	.33	B 57	.69	B 89	1.08	B 122	1.44	B 164	2.08	B 245	2.82
B 27	.34	B 58	.72	B 90	1.09	B 123	1.45	B 165	2.09	B 248	2.83
B 28	.35	B 59	.73	B 91	1.10	B 124	1.47	B 166	2.09	B 249	2.83
B 29	.36	B 60	.74	B 92	1.11	B 125	1.48	B 167	2.10	B 250	2.84
B 30	.37	B 61	.75	B 93	1.12	B 126	1.49	B 168	2.12	B 251	2.84
B 31	.38	B 62	.76	B 94	1.13	B 127	1.50	B 169	2.12	B 253	2.85
B 32	.40	B 63	.77	B 95	1.15	B 128	1.51	B 173	2.12	B 255	2.86
B 33	.41	B 64	.78	B 96	1.16	B 130	1.53	B 174	2.13	B 259	2.87
B 34	.42	B 65	.81	B 97	1.17	B 131	1.54	B 175	2.14	B 265	2.88
B 35	.43	B 66	.82	B 98	1.18	B 132	1.55	B 178	2.25	B 270	2.88
B 36	.44	B 67	.83	B 99	1.19	B 133	1.58	B 180	2.27	B 275	2.89
B 37	.45	B 68	.84	B 100	1.20	B 134	1.59	B 185	2.38	B 275.5	2.89
B 38	.46	B 69	.85	B 101	1.21	B 135	1.60	B 188	2.41	B 276	2.90
B 39	.48	B 70	.86	B 102	1.22	B 136	1.61	B 189	2.44	B 280	2.90
B 40	.49	B 71	.87	B 103	1.23	B 137	1.61	B 190	2.45	B 285	2.90
B 41	.50	B 72	.88	B 104	1.24	B 138	1.62	B 191	2.46	B 292	2.95
B 42	.51	B 73	.89	B 105	1.26	B 140	1.66	B 192	2.47	B 293	2.97
B 43	.52	B 74	.90	B 106	1.27	B 142	1.66	B 193	2.48	B 300	3.00
B 44	.54	B 75	.91	B 107	1.28	B 144	1.76	B 195	2.49	B 315	3.20
B 45	.55	B 76	.92	B 108	1.29	B 146	1.79	B 200	2.55	B 330	3.65
B 46	.57	B 77	.93	B 109	1.30	B 147	1.83	B 205	2.56	B 340	3.75
B 47	.58	B 78	.94	B 110	1.31	B 148	1.84	B 206	2.59	B 346	3.80
B 48	.59	B 79	.95	B 111	1.32	B 150	1.86	B 208	2.61	B 354	3.85
B 48.5	.59	B 80	.96	B 112	1.33	B 152	1.88	B 210	2.66	B 360	3.89
B 49	.60	B 81	1.00	B 113	1.34	B 153	1.90	B 213	2.68	B 433	4.00
B 50	.61	B 82	1.00	B 114	1.36	B 154	1.91	B 217	2.69	B 512	5.00
B 51	.63	B 83	1.01	B 115	1.37	B 156	1.93	B 221	2.70		
B 52	.64	B 84	1.02	B 116	1.38	B 157	1.94	B 225	2.72		
B 53	.65	B 85	1.03	B 117	1.39	B 158	1.95	B 229	2.78		

American Standard Classical V-Belts



C

Section C (7/8" x 9/16")

Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)
C 38	1.02	C 72	1.45	C 104	2.07	C 143	3.16	C 183	3.75	C 260	5.30
C 40	1.03	C 73	1.46	C 105	2.08	C 144	3.17	C 185	3.80	C 262	5.34
C 42	1.04	C 74	1.47	C 106	2.11	C 145	3.18	C 188	3.85	C 268	5.38
C 43	1.04	C 75	1.50	C 107	2.12	C 146	3.19	C 190	3.89	C 270	5.40
C 44	1.05	C 76	1.52	C 108	2.13	C 147	3.26	C 195	4.01	C 272	5.44
C 45	1.06	C 77	1.55	C 109	2.16	C 148	3.27	C 196	4.02	C 280	5.48
C 46	1.07	C 78	1.56	C 110	2.18	C 150	3.33	C 197	4.04	C 285	5.50
C 48	1.09	C 79	1.59	C 111	2.21	C 151	3.34	C 198	4.05	C 298	5.60
C 49	1.10	C 80	1.60	C 112	2.44	C 152	3.35	C 200	4.06	C 300	5.65
C 50	1.11	C 81	1.62	C 114	2.49	C 153	3.36	C 201	4.07	C 315	5.80
C 51	1.12	C 82	1.63	C 115	2.50	C 154	3.37	C 202	4.08	C 328	5.90
C 52	1.16	C 83	1.65	C 116	2.51	C 155	3.38	C 204	4.42	C 330	6.00
C 53	1.17	C 84	1.67	C 117	2.52	C 156	3.39	C 205	4.43	C 340	6.20
C 54	1.18	C 85	1.70	C 118	2.54	C 158	3.45	C 206	4.44	C 345	6.30
C 55	1.20	C 86	1.71	C 119	2.56	C 160	3.49	C 207	4.45	C 348	6.35
C 56	1.21	C 87	1.73	C 120	2.59	C 162	3.52	C 208	4.46	C 349	6.40
C 57	1.25	C 88	1.74	C 122	2.63	C 163	3.53	C 209	4.47	C 358	6.60
C 58	1.26	C 90	1.79	C 123	2.65	C 164	3.54	C 210	4.48	C 360	6.75
C 59	1.31	C 91	1.80	C 124	2.67	C 165	3.55	C 212	4.52	C 390	7.10
C 60	1.32	C 92	1.83	C 126	2.69	C 166	3.56	C 215	4.61	C 418	7.60
C 61	1.33	C 93	1.85	C 128	2.75	C 167	3.57	C 218	4.83	C 420	7.70
C 62	1.36	C 94	1.86	C 130	2.79	C 168	3.57	C 220	5.00	C 450	7.80
C 63	1.38	C 95	1.89	C 131	2.80	C 169	3.58	C 225	5.02	C 480	8.00
C 64	1.41	C 96	1.90	C 134	3.00	C 170	3.58	C 228	5.04		
C 65	1.42	C 97	1.93	C 135	3.01	C 173	3.59	C 230	5.06		
C 66	1.43	C 98	1.94	C 136	3.02	C 174	3.59	C 238	5.08		
C 67	1.44	C 99	1.97	C 137	3.03	C 175	3.60	C 240	5.10		
C 68	1.45	C 100	1.99	C 138	3.08	C 177	3.62	C 245	5.15		
C 69	1.45	C 101	2.01	C 140	3.10	C 178	3.69	C 246	5.17		
C 70	1.46	C 102	2.04	C 141	3.11	C 180	3.72	C 250	5.19		
C 71	1.46	C 103	2.05	C 142	3.12	C 182	3.73	C 255	5.20		

D


Section D (1 1/4" x 3/4")

Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)
D 75	4.00	D 125	4.50	D 171	6.10	D 238	8.30	D 300	10.50	D 418	14.60
D 88	4.10	D 128	4.60	D 173	6.10	D 240	8.40	D 310	10.75	D 420	14.70
D 90	4.15	D 136	4.79	D 175	6.30	D 248	8.70	D 314	10.90	D 450	15.70
D 91	4.20	D 143	5.00	D 180	6.40	D 250	8.80	D 315	11.00	D 477	16.80
D 95	4.25	D 144	5.10	D 195	7.06	D 255	8.90	D 328	11.25	D 480	16.80
D 105	4.30	D 158	5.60	D 200	7.15	D 268	9.30	D 330	11.50	D 536	17.80
D 107	4.30	D 162	5.70	D 204	7.20	D 270	9.40	D 345	12.00	D 540	18.90
D 112	4.30	D 165	5.73	D 205	7.30	D 280	9.75	D 358	12.60	D 595	19.50
D 114	4.30	D 167	5.75	D 210	7.40	D 285	9.90	D 360	12.88	D 600	20.90
D 120	4.30	D 170	6.00	D 225	7.90	D 298	10.20	D 390	13.60	D 660	23.00

E

Section E (1 1/2" x 1")

Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)
E 180	10.10	E 236	13.10	E 297	16.30	E 357	14.65	E 418	22.80	E 538	30.00
E 195	10.65	E 240	13.15	E 300	16.44	E 360	14.73	E 420	22.99	E 598	34.00
E 210	11.72	E 266	14.65	E 328	18.05	E 390	21.37	E 478	26.10		
E 225	12.35	E 270	14.79	E 330	18.09	E 394	22.00	E 480	27.00		




American Metric® Corporation

GROUP: 083

1-083-050118

American Standard Classical Raw Edged Cogged V-Belts



AX

Section AX (1/2" x 11/32")




Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)
AX 20	.16	AX 37	.24	AX 54	.34	AX 71	.50	AX 88	.58	AX 115	.75
AX 21	.16	AX 38	.24	AX 55	.36	AX 72	.50	AX 89	.58	AX 116	.77
AX 22	.16	AX 39	.26	AX 56	.36	AX 73	.50	AX 90	.59	AX 118	.78
AX 23	.16	AX 40	.26	AX 57	.36	AX 74	.50	AX 91	.59	AX 120	.79
AX 24	.18	AX 41	.26	AX 58	.38	AX 75	.50	AX 92	.60	AX 124	.80
AX 25	.18	AX 42	.28	AX 59	.38	AX 76	.51	AX 93	.61	AX 125	.81
AX 26	.18	AX 43	.28	AX 60	.38	AX 77	.52	AX 94	.62	AX 128	.83
AX 27	.18	AX 44	.28	AX 61	.40	AX 78	.52	AX 95	.63	AX 130	.87
AX 28	.18	AX 45	.30	AX 62	.40	AX 79	.53	AX 96	.63	AX 134	.89
AX 29	.20	AX 46	.30	AX 63	.40	AX 80	.53	AX 97	.64	AX 136	.90
AX 30	.20	AX 47	.30	AX 64	.40	AX 81	.53	AX 98	.65	AX 140	.93
AX 31	.20	AX 48	.30	AX 65	.42	AX 82	.54	AX 100	.65	AX 144	.95
AX 32	.20	AX 49	.32	AX 66	.44	AX 83	.55	AX 105	.69	AX 158	1.04
AX 33	.22	AX 50	.32	AX 67	.45	AX 84	.55	AX 107	.71	AX 160	1.13
AX 34	.22	AX 51	.32	AX 68	.45	AX 85	.56	AX 108	.72	AX 173	1.14
AX 35	.22	AX 52	.34	AX 69	.46	AX 86	.57	AX 110	.73	AX 180	1.19
AX 36	.24	AX 53	.34	AX 70	.46	AX 87	.58	AX 112	.74		

BX

Section BX (21/32" x 7/16")

Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)
BX 24	-	BX 45	.44	BX 66	.62	BX 88	.85	BX 117	1.11	BX 162	1.51
BX 25	-	BX 46	.44	BX 67	.63	BX 89	.86	BX 118	1.11	BX 168	1.58
BX 26	-	BX 47	.46	BX 68	.64	BX 90	.87	BX 120	1.12	BX 169	1.60
BX 27	-	BX 48	.46	BX 69	.66	BX 91	.87	BX 122	1.13	BX 173	1.62
BX 28	.28	BX 48.5	.47	BX 70	.67	BX 92	.87	BX 123	1.14	BX 180	1.68
BX 29	-	BX 49	.48	BX 71	.68	BX 93	.87	BX 124	1.16	BX 190	1.90
BX 30	-	BX 50	.48	BX 72	.68	BX 94	.88	BX 128	1.20	BX 195	2.00
BX 31	-	BX 51	.48	BX 73	.69	BX 95	.89	BX 130	1.23	BX 205	2.07
BX 32	.30	BX 52	.50	BX 74	.70	BX 96	.90	BX 132	1.24	BX 210	2.10
BX 33	-	BX 53	.50	BX 75	.70	BX 97	.91	BX 133	1.25	BX 225	2.30
BX 34	.32	BX 54	.52	BX 76	.71	BX 98	.92	BX 134	1.26	BX 238	2.35
BX 35	.34	BX 55	.52	BX 77	.72	BX 99	.93	BX 136	1.27	BX 240	2.40
BX 36	.36	BX 56	.54	BX 78	.73	BX 100	.94	BX 140	1.30	BX 255	2.50
BX 37	-	BX 57	.56	BX 79	.74	BX 102	.96	BX 142	1.34	BX 270	2.70
BX 38	.36	BX 58	.56	BX 80	.75	BX 103	.97	BX 144	1.35	BX 275	2.90
BX 39	-	BX 59	.56	BX 81	.76	BX 104	.98	BX 146	1.36	BX 275.5	2.90
BX 40	.38	BX 60	.56	BX 82	.77	BX 105	.98	BX 148	1.37	BX 300	3.00
BX 41	.40	BX 61	.58	BX 83	.78	BX 108	1.01	BX 150	1.40		
BX 41.5	.40	BX 62	.58	BX 84	.79	BX 110	1.05	BX 152	1.43		
BX 42	.40	BX 63	.59	BX 85	.80	BX 112	1.05	BX 154	1.44		
BX 43	.42	BX 64	.60	BX 86	.82	BX 115	1.08	BX 156	1.47		
BX 44	.42	BX 65	.61	BX 87	.83	BX 116	1.10	BX 158	1.48		

American Standard Classical Raw Edged Cogged V-Belts



CX

Section CX (7/8" x 9/16")



Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)
CX 40	1	CX 59	1.15	CX 77	1.33	CX 111	1.90	CX 147	2.59	CX 240	3.90
CX 42	1	CX 60	1.20	CX 78	1.35	CX 112	1.92	CX 150	2.62	CX 255	4.10
CX 43	1	CX 61	1.22	CX 79	1.37	CX 115	1.97	CX 152	2.68	CX 268	4.25
CX 44	1	CX 62	1.23	CX 80	1.38	CX 116	1.99	CX 158	2.69	CX 270	4.40
CX 45	1	CX 63	1.24	CX 81	1.39	CX 118	2.03	CX 162	2.80	CX 285	4.65
CX 48	1	CX 64	1.24	CX 85	1.46	CX 120	2.05	CX 173	3.00	CX 298	4.85
CX 50	1.02	CX 65	1.24	CX 90	1.55	CX 123	2.07	CX 180	3.10	CX 300	4.90
CX 51	1.02	CX 67	1.25	CX 93	1.60	CX 124	2.10	CX 185	3.15	CX 315	5.10
CX 52	1.03	CX 68	1.25	CX 96	1.65	CX 126	2.15	CX 187	3.18	CX 328	5.20
CX 53	1.04	CX 69	1.26	CX 100	1.69	CX 128	2.19	CX 190	3.19	CX 330	5.30
CX 54	1.04	CX 71	1.26	CX 101	1.72	CX 130	2.27	CX 195	3.20	CX 345	5.60
CX 55	1.05	CX 72	1.27	CX 105	1.80	CX 133	2.30	CX 204	3.35	CX 358	5.70
CX 56	1.07	CX 73	1.28	CX 106	1.85	CX 136	2.32	CX 210	3.40	CX 360	5.80
CX 57	1.09	CX 75	1.30	CX 108	1.86	CX 140	2.43	CX 225	3.60	CX 418	6.60
CX 58	1.10	CX 76	1.31	CX 109	1.87	CX 144	2.46	CX 238	3.85		

DX

Section DX (1 1/4" x 3/4")

Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)	Part No.	Wt. (lbs)
DX 75	4.50	DX 120	4.60	DX 173	6.60	DX 238	8.50	DX 358	11.00	DX 536	14.00
DX 88	4.50	DX 128	4.90	DX 180	6.80	DX 268	9.00	DX 390	11.50	DX 595	15.00
DX 90	4.50	DX 143	5.95	DX 195	7.40	DX 298	9.50	DX 418	12.00		
DX 91	4.50	DX 158	6.00	DX 204	7.95	DX 314	10.00	DX 450	12.50		
DX 95	4.50	DX 162	6.20	DX 210	8.00	DX 328	10.50	DX 477	13.00		

American Standard Wedged V-Belts



3V / 9N

Part No.	Outside Length (inches)	Metric No.	Wt. (lbs)
3V 250	25.0	9XN630	0.1
3V 265	26.5	9XN670	0.1
3V 280	28.0	9XN710	0.1
3V 300	30.0	9XN760	0.1
3V 315	31.5	9XN800	0.1
3V 320	32.0	-	0.1
3V 335	33.5	9XN850	0.1
3V 340	34.0	-	0.2
3V 350	35.0	-	0.2
3V 355	35.5	9XN900	0.2
3V 360	36.0	-	0.2
3V 375	37.5	9XN950	0.2
3V 380	38.0	-	0.2
3V 400	40.0	9XN1015	0.2
3V 425	42.4	9XN1080	0.2
3V 450	45.0	9XN1145	0.2
3V 475	47.5	9XN1205	0.2
3V 500	50.0	9XN1270	0.2
3V 530	53.0	9XN1345	0.2
3V 560	56.0	9XN1420	0.2
3V 600	60.0	9XN1525	0.3
3V 630	63.0	9XN1600	0.3
3V 650	65.0	-	0.3
3V 670	67.0	9XN1700	0.3
3V 675	67.5	-	0.3
3V 700	70.0	-	0.3
3V 710	71.0	9XN1800	0.3
3V 750	75.0	9XN1900	0.3
3V 800	80.0	9XN2030	0.4
3V 830	83.0	-	0.4
3V 850	85.0	9XN2160	0.4
3V 900	90.0	9XN2290	0.4
3V 920	92.0	-	0.4
3V 950	95.0	9XN2410	0.4
3V 1000	100.0	9XN2540	0.4
3V 1060	106.0	9XN2690	0.5
3V 1120	112.0	9XN2840	0.5
3V 1180	118.0	9XN3000	0.6
3V 1200	120.0	-	0.6
3V 1250	125.0	9XN3180	0.6
3V 1320	132.0	9XN3350	0.7
3V 1400	140.0	9XN3550	0.7
3V 1500	150.0	9XN3810	0.7




5V / 15N

Part No.	Outside Length (inches)	Metric No.	Wt. (lbs)
5V 315	31.5	15N	-
5V 400	40.0	15N	-
5V 425	42.5	15N	-
5V 450	45.0	15N	-
5V 500	50.0	15N	-
5V 530	43.0	15N	-
5V 560	56.0	15N	-
5V 600	60.0	15N	-
5V 620	62.0	15N	-
5V 630	63.0	15N	-
5V 670	67.0	15N	-
5V 700	70.0	15N	-
5V 710	71.0	15N	-
5V 750	75.0	15N	-
5V 800	80.0	15N	-
5V 850	85.0	15N	-
5V 900	90.0	15N	-
5V 950	95.0	15N	-
5V 1000	100.0	15N	-
5V 1030	103.0	15N	-
5V 1060	106.0	15N	-
5V 1120	112.0	15N	-
5V 1130	113.0	15N	-
5V 1180	118.0	15N	-
5V 1250	125.0	15N	-
5V 1320	132.0	15N	-
5V 1400	140.0	15N	-
5V 1500	150.0	15N	-
5V 1600	160.0	15N	-
5V 1700	170.0	15N	-
5V 1800	180.0	15N	-
5V 1900	190.0	15N	-
5V 2000	200.0	15N	-
5V 2120	212.0	15N5380	2.5
5V 2240	224.0	15N5690	2.7
5V 2360	236.0	15N6000	2.8
5V 2500	250.0	15N6350	3.0
5V 2650	265.0	15N6730	3.2
5V 2800	280.0	15N7100	3.3
5V 3000	300.0	15N7620	3.6
5V 3150	315.0	15N8000	3.8
5V 3350	335.0	15N8500	4.1
5V 3550	355.0	15N9000	4.3

8V / 25N

Part No.	Outside Length (inches)	Metric No.	Wt. (lbs)
8V 1000	100.0	25N	-
8V 1060	106.0	25N	-
8V 1120	112.0	25N	-
8V 1180	118.0	25N	-
8V 1250	125.0	25N	-
8V 1320	132.0	25N	-
8V 1400	140.0	25N	-
8V 1500	150.0	25N	-
8V 1600	160.0	25N	-
8V 1700	170.0	25N	-
8V 1800	180.0	25N	-
8V 1900	190.0	25N	-
8V 2000	200.0	25N	-
8V 2120	212.0	25N5380	7.5
8V 2240	224.0	25N5690	7.9
8V 2360	236.0	25N6000	8.3
8V 2500	250.0	25N6350	8.8
8V 2600	260.0	25N	-
8V 2650	265.0	25N6730	9.3
8V 2800	280.0	25N7100	9.8
8V 3000	300.0	25N7620	10.5
8V 3150	315.0	25N8000	11.1
8V 3350	335.0	25N8500	11.8
8V 3550	355.0	25N8999	12.5
8V 3750	375.0	25N9500	13.7
8V 4000	400.0	25N10160	14.0
8V 4250	425.0	25N10800	14.9
8V 4500	450.0	25N11430	15.8
8V 4750	475.0	25N12060	16.7
8V 5000	500.0	25N12700	17.6
8V 5600	560.0	25N	-
8V 5900	590.0	25N	-

American Standard Wedged Raw Edged Cogged V-Belts



3VX / 9N

Part No.	Outside Length (inches)	Metric No.	Wt. (lbs)
3VX 240	24.0	9XN	0.1
3VX 250	25.0	9XN630	0.1
3VX 255	25.5	9XN	0.1
3VX 265	26.5	9XN670	0.1
3VX 280	28.0	9XN710	0.1
3VX 300	30.0	9XN760	0.1
3VX 315	31.5	9XN800	0.1
3VX 335	33.5	9XN850	0.1
3VX 340	34.0	9XN	0.1
3VX 355	35.5	9XN900	0.2
3VX 360	36.0	9XN	0.2
3VX 375	37.5	9XN950	0.2
3VX 400	40.0	9XN1015	0.2
3VX 425	42.5	9XN1080	0.2
3VX 450	45.0	9XN1145	0.2
3VX 475	47.5	9XN1205	0.2
3VX 500	50.0	9XN1270	0.2
3VX 530	53.0	9XN1345	0.2
3VX 560	56.0	9XN1420	0.2
3VX 600	60.0	9XN1525	0.3
3VX 630	63.0	9XN1600	0.3
3VX 670	67.0	9XN1700	0.3
3VX 710	71.0	9XN1800	0.3
3VX 750	75.0	9XN1900	0.3
3VX 800	80.0	9XN2030	0.4
3VX 850	85.0	9XN2160	0.4
3VX 900	90.0	9XN2290	0.4
3VX 950	95.0	9XN2410	0.4
3VX 1000	100.0	9XN2540	0.4
3VX 1060	106.0	9XN2690	0.5
3VX 1120	112.0	9XN2840	0.5
3VX 1180	118.0	9XN3000	0.6
3VX 1250	125.0	9XN3180	0.6
3VX 1320	132.0	9XN3350	0.7
3VX 1400	140.0	9XN3550	0.7
3VX 1500	150.0	9XN3810	0.7

5VX / 15N

Part No.	Outside Length (inches)	Metric No.	Wt. (lbs)
5VX 315	31.5	15XN	0.6
5VX 400	40.0	15XN	0.6
5VX 425	42.5	15XN	0.6
5VX 450	45.0	15XN1150	0.6
5VX 500	50.0	15XN1270	0.6
5VX 530	53.0	15XN1345	0.7
5VX 560	56.0	15XN1420	0.7
5VX570	57.0	15XN1450	0.7
5VX580	58.0	15XN1470	0.7
5VX590	59.0	15XN1500	0.7
5VX 600	60.0	15XN1525	0.7
5VX610	61.0	15XN1550	0.7
5VX 630	63.0	15XN1600	0.7
5VX650	65.0	15XN1650	0.8
5VX 670	67.0	15XN1700	0.8
5VX 700	70.0	15XN	0.8
5VX 710	71.0	15XN1800	0.8
5VX 750	75.0	15XN1900	0.8
5VX780	78.0	15XN1980	.8
5VX 800	80.0	15XN2030	0.9
5VX840	84.0	15XN2130	0.9
5VX 850	85.0	15XN2160	0.9
5VX860	86.0	15XN2180	0.9
5VX880	88.0	15XN2240	0.9
5VX 900	90.0	15XN2290	1.1
5VX 950	95.0	15XN2410	1.1
5VX 1000	100.0	15XN2540	1.2
5VX 1060	106.0	15XN2690	1.2
5VX 1120	112.0	15XN2840	1.3
5VX1150	115.0	15XN2920	1.4
5VX 1180	118.0	15XN3000	1.4
5VX1180	123	15XN3130	1.5
5VX 1250	125.0	15XN3180	1.5
5VX 1320	132.0	15XN3350	1.6
5VX 1400	140.0	15XN3550	1.7
5VX 1500	150.0	15XN3810	1.8
5VX 1600	160.0	15XN4060	1.9
5VX 1700	170.0	15XN4320	2.0
5VX 1800	180.0	15XN4570	2.1
5VX 1900	190.0	15XN4830	2.3
5VX 2000	200.0	15XN5080	2.4

8VX / 25N

Part No.	Outside Length (inches)	Metric No.	Wt. (lbs)
8VX 1000	100.0	25XN2540	2.9
8VX 1060	106.0	25XN2690	3.0
8VX 1120	112.0	25XN2840	3.2
8VX 1180	118.0	25XN3000	3.4
8VX 1250	125.0	25XN3180	3.6
8VX 1320	132.0	25XN3350	3.8
8VX 1400	140.0	25XN3550	4.0
8VX 1500	150.0	25XN3810	4.3
8VX 1600	160.0	25XN4060	4.6
8VX 1700	170.0	25XN4320	4.9
8VX 1800	180.0	25XN4570	5.2
8VX 1900	190.0	25XN4830	5.5
8VX 2000	200.0	25XN5080	5.7