


Keyless Self-Locking Bushing



Type 1108

Part No.	Dimensions (mm)					Performances		Screws				Set Screws			
	d	H	H1	H2	D	Mt (Nm)	Pax (N)	N°	Type	Ms (Nm)	Key	N°	Type	Ms (Nm)	Key
SL1108F12	12	20	28.8	32.8	39	40	6600	6	M4	4.9	3	2	1/4 W	4.9	3
SL1108F14	14	20	28.8	32.8	39	56	8000	6	M4	4.9	3	2	1/4 W	4.9	3
SL1108F15	15	20	28.8	32.8	39	85	11300	6	M4	4.9	3	2	1/4 W	4.9	3
SL1108F16	16	20	28.8	32.8	39	100	12500	6	M4	4.9	3	2	1/4 W	4.9	3
SL1108F18	18	20	28.8	32.8	39	120	13300	6	M4	4.9	3	2	1/4 W	4.9	3
SL1108F19	19	20	28.8	32.8	39	128	13500	6	M4	4.9	3	2	1/4 W	4.9	3
SL1108F20	20	20	28.8	32.8	39	136	13600	6	M4	4.9	3	2	1/4 W	4.9	3
SL1108F22	22	20	28.8	32.8	39	150	13650	6	M4	4.9	3	2	1/4 W	4.9	3

Type 1210

SL1210F14	14	25	34.8	40.8	49	100	14300	6	M6	17	5	2	3/8 W	17	5
SL1210F15	15	25	34.8	40.8	49	115	15300	6	M6	17	5	2	3/8 W	17	5
SL1210F16	16	25	34.8	40.8	49	130	16250	6	M6	17	5	2	3/8 W	17	5
SL1210F18	18	25	34.8	40.8	49	160	17800	6	M6	17	5	2	3/8 W	17	5
SL1210F19	19	25	34.8	40.8	49	175	18400	6	M6	17	5	2	3/8 W	17	5
SL1210F20	20	25	34.8	40.8	49	190	19000	6	M6	17	5	2	3/8 W	17	5
SL1210F22	22	25	34.8	40.8	49	270	24500	6	M6	17	5	2	3/8 W	17	5
SL1210F24	24	25	34.8	40.8	49	340	28300	6	M6	17	5	2	3/8 W	17	5
SL1210F25	25	25	34.8	40.8	49	400	32000	6	M6	17	5	2	3/8 W	17	5

Type 1610

SL1610F14	14	25	34.8	40.8	59	100	14300	6	M6	17	5	2	3/8 W	17	5
SL1610F15	15	25	34.8	40.8	59	115	15300	6	M6	17	5	2	3/8 W	17	5
SL1610F16	16	25	34.8	40.8	59	130	16250	6	M6	17	5	2	3/8 W	17	5
SL1610F18	18	25	34.8	40.8	59	160	17800	6	M6	17	5	2	3/8 W	17	5
SL1610F19	19	25	34.8	40.8	59	175	18400	6	M6	17	5	2	3/8 W	17	5
SL1610F20	20	25	34.8	40.8	59	190	19000	6	M6	17	5	2	3/8 W	17	5
SL1610F22	22	25	34.8	40.8	59	220	20000	6	M6	17	5	2	3/8 W	17	5
SL1610F24	24	25	34.8	40.8	59	250	20800	6	M6	17	5	2	3/8 W	17	5
SL1610F25	25	25	34.8	40.8	59	265	21200	6	M6	17	5	2	3/8 W	17	5
SL1610F28	28	25	34.8	40.8	59	310	22150	6	M6	17	5	2	3/8 W	17	5
SL1610F30	30	25	34.8	40.8	59	340	22700	6	M6	17	5	2	3/8 W	17	5
SL1610F32	32	25	34.8	40.8	59	380	23750	6	M6	17	5	2	3/8 W	17	5
SL1610F35	35	25	34.8	40.8	59	420	24000	6	M6	17	5	2	3/8 W	17	5




American Metric® Corporation

GROUP: 057

1-057 - 010105

Keyless Self-Locking Bushing



Type 2012

Part No.	Dimensions (mm)					Performances		Screws				Set Screws			
	d	H	H1	H2	D	Mt (Nm)	Pax (N)	N°	Type	Ms (Nm)	Key	N°	Type	Ms (Nm)	Key
SL2012F19	19	30	40.8	48.8	71	150	15800	6	M8	41	6	2	7/16 W	41	6
SL2012F20	20	30	40.8	48.8	71	180	18000	6	M8	41	6	2	7/16 W	41	6
SL2012F22	22	30	40.8	48.8	71	210	19100	6	M8	41	6	2	7/16 W	41	6
SL2012F24	24	30	40.8	48.8	71	280	23300	6	M8	41	6	2	7/16 W	41	6
SL2012F25	25	30	40.8	48.8	71	350	28000	6	M8	41	6	2	7/16 W	41	6
SL2012F28	28	30	40.8	48.8	71	500	35700	6	M8	41	6	2	7/16 W	41	6
SL2012F30	30	30	40.8	48.8	71	580	38700	6	M8	41	6	2	7/16 W	41	6
SL2012F32	32	30	40.8	48.8	71	650	40600	6	M8	41	6	2	7/16 W	41	6
SL2012F35	35	30	40.8	48.8	71	800	45700	6	M8	41	6	2	7/16 W	41	6
SL2012F38	38	30	40.8	48.8	71	900	47400	6	M8	41	6	2	7/16 W	41	6
SL2012F40	40	30	40.8	48.8	71	990	49500	6	M8	41	6	2	7/16 W	41	6
SL2012F42	42	30	40.8	48.8	71	1100	52400	6	M8	41	6	2	7/16 W	41	6

Type 2517

SL2517F24	24	45	55.8	63.8	86	280	23300	6	M8	41	6	2	1/2 W	41	6
SL2517F25	25	45	55.8	63.8	86	350	28000	6	M8	41	6	2	1/2 W	41	6
SL2517F28	28	45	55.8	63.8	86	500	35700	6	M8	41	6	2	1/2 W	41	6
SL2517F30	30	45	55.8	63.8	86	580	38700	6	M8	41	6	2	1/2 W	41	6
SL2517F32	32	45	55.8	63.8	86	650	40600	6	M8	41	6	2	1/2 W	41	6
SL2517F35	35	45	55.8	63.8	86	800	45700	6	M8	41	6	2	1/2 W	41	6
SL2517F38	38	45	55.8	63.8	86	900	47300	6	M8	41	6	2	1/2 W	41	6
SL2517F40	40	45	55.8	63.8	86	990	49500	6	M8	41	6	2	1/2 W	41	6
SL2517F42	42	45	55.8	63.8	86	1100	52400	6	M8	41	6	2	1/2 W	41	6
SL2517F45	45	45	55.8	63.8	86	1360	60500	6	M8	41	6	2	1/2 W	41	6
SL2517F48	48	45	55.8	63.8	86	1640	68300	6	M8	41	6	2	1/2 W	41	6
SL2517F50	50	45	55.8	63.8	86	1650	74000	6	M8	41	6	2	1/2 W	41	6
SL2517F55	55	45	55.8	63.8	86	2100	76300	6	M8	41	6	2	1/2 W	41	6

Type 3020

SL3020F35	35	50	62.8	72.8	108	810	46300	6	M10	83	8	2	5/8 W	83	8
SL3020F38	38	50	62.8	72.8	108	960	50500	6	M10	83	8	2	5/8 W	83	8
SL3020F40	40	50	62.8	72.8	108	1200	60000	6	M10	83	8	2	5/8 W	83	8
SL3020F42	42	50	62.8	72.8	108	1580	75300	6	M10	83	8	2	5/8 W	83	8
SL3020F45	45	50	62.8	72.8	108	2000	89000	6	M10	83	8	2	5/8 W	83	8
SL3020F48	48	50	62.8	72.8	108	2140	90000	6	M10	83	8	2	5/8 W	83	8
SL3020F50	50	50	62.8	72.8	108	2310	92400	6	M10	83	8	2	5/8 W	83	8
SL3020F55	55	50	62.8	72.8	108	2530	92000	6	M10	83	8	2	5/8 W	83	8
SL3020F60	60	50	62.8	72.8	108	2950	98300	6	M10	83	8	2	5/8 W	83	8
SL3020F65	65	50	62.8	72.8	108	3360	103400	6	M10	83	8	2	5/8 W	83	8
SL3020F70	70	50	62.8	72.8	108	4100	118000	6	M10	83	8	2	5/8 W	83	8