


O-Ring Chain

Automotive O-Ring Chains (Also For Industrial Application)

Ametric Part Number	Pitch (P)	Width between Inner Plates (W) (Min)	Roller Diameter (D) (Max)	Bearing Pin Diameter (d) (Max)	Breaking Load
J415 OR	12.70	5.15	7.75	4.07	2,200 3,200 3,200 3,600 4,200 3,600
J428 OR	12.70	7.95	8.51	4.46	
J520 OR	15.875	6.38	10.16	5.30	
J525 OR	15.875	7.95	10.16	5.30	
J530 OR	15.875	9.52	10.16	5.30	
J630 OR	19.05	9.52	11.90	5.95	
J460 OR	19.05	12.7	11.90	5.95	



Other O-Ring Chains

Intl. Ref. No.	Ametric Part Number	Pitch (P)	Width between Inner Plates (W) (Min)	Roller Diameter (D) (Max)	IP Height (H1) (Max)	OP Height (H2) (Max)	IP Thickness (T1) (Max)	OP Thickness (T2) (Max)	Width Over Bearing Pin (A) (Max)	Bearing Pin Diameter (d) (Max)	Width Over Joint Fasteners (B)	Average Weight Per Meter (Kg)	Tensile Strength KN (Min)
08B OR	42 OR	12.70	7.75	8.51	11.56	10.57	1.58	1.50	19.00	4.45	20.30	0.693	185.59
10B OR	52 OR	15.875	9.65	10.16	14.48	13.51	1.58	1.58	21.94	5.06	23.53	0.921	231.48

Ametric O-Ring Chain with unique design are engineered to offer superior resistance to wear.

